CEMO
for safe storage

DATASHEET

Battery safety storage cabinet 12/20 door orange RAL 2008

Order number: 11961

DESCRIPTION

- safe 2-point locking for optimal access protection
- locking mechanism activates automatically when closing the doors
- maintenance opening for the door locking mechanism
- self-closing doors in the event of a fire
- arresting the door in open position, as standard
- magnetic lock ensures that the doors are fully locked and perfectly sealed
- height-adjustable shelves, 32 mm grid dimension
- added safety: tested load detection for weight of a fan on the top of the cabinet
- in case of fire, self-closing vents on the top of the cabinet, ready for connection to mechanical ventilation (DN 75 mm)
- forkliftable thanks to feet that are height-adjustable from inside and removable base trim
- earthing point on the outside prevents electrostatic charging
- optional: cable duct for installation of measuring equipment
- optional: equipotential bonding of the shelves for active storage









TECHNICAL DATA

Collection volume	33 l
External dimensions (w x d x h)	120 x 60 x 195 cm
Internal dimensions (w x d x h)	105 x 49 x 166 cm
Weight	450 kg
Fire Resistance	F90
Installation Location	indoor
Material	non-combustible building material
Coating	Melaminharz (innen) / Pulverbeschichtung (außen)
Container Colour	grey
Door Colour	orange
Operating Voltage	- / -
Load Capacity per Storage Level	300 kg
Stackable	no

Forkliftable	yes

EQUIPMENT

Feet/Castors	mit Füßen
Number of Doors	2
Door Model	double hinged doors
Lock Type	self-closing, 2-point locking
Mechanical Ventilation	-
Number of Power Sockets	-
Storage Levels	4
Number of Shelves	3
Shelf Material	powder-coated steel
Smoke Detector	battery-powered
Warning Signal	audible
Internal Volt-Free Contact	no

SUITABLE MEDIA

Lithium Batteries

LOGISTICS

Package dimensions (lxwxh)	67 x 120 x 197 cm
Pallet Dimensions	80 x 120 x 211 cm
Package Weight	480 kg
Freight	General cargo

APPROVAL

DIN/EN Approval	EN 14470-1

ACCESSORIES



8739 - Extraction system with fan and air flow monitoring



10963 - Recirculation fan SST UL with adapter SST-P for type FWF90



11431 - Radial fan 230 V (model 1)



11432 - Radial fan 230 V (model 2)



11433 - Radial fan 380 V (model 3)



11881 - Shelf 12/20 cpl. packed



11884 - Cable duct 6/20 and 12/20 (in cabinet ceiling, fro self-assembly)



11994 - Additional floor plate 12/20 stainless steel for PROline 12/20



12074 - Accessory Pack fro active storage for PROline 6/20 and 12/20



12077 - Spare key for PROline

Link to product

Subject to technical changes/errors. © CEMO 11961-en 04.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com